



# T800-EX FULLY RUGGED TABLET

- 8.1" HD LumiBond® 2.0 display for better viewing experience
- MIL-STD-810H and IP65 certified
- Enhanced Enterprise Security with TPM2.0, Windows Disk Encryption



SnapBack add-on



# Specifications

## Operating System

Windows 10 Pro

## Mobile Computing Platform

Intel® Atom Processor x7-Z8750 1.6GHz, burst up to 2.56GHz  
- 2MB Cache

## VGA Controller

Intel® HD Graphics

## Display

8.1" IPS TFT LCD HD (1280 x 800)  
Protection film  
600 nits LumiBond® display with Getac sunlight readable technology

## Storage & Memory

4GB LPDDR3  
Optional: 8GB LPDDR3  
128GB eMMC  
Optional: 256GB eMMC

## Keyboard

Power button  
5 tablet programmable buttons

## Pointing Device

Touchscreen  
- Capacitive multi-touch screen  
- Optional: Dual mode touchscreen (multi-touch and digitizer)

## Expansion Slot

Optional: 1D / 2D imager barcode reader x1

## I/O Interface

FHD webcam x 1  
8M pixels auto focus rear camera x 1  
Headphone out/Mic-in Combo x 1  
DC in Jack x 1  
USB 3.2 Gen 1 Type-A x 1  
Micro HDMI x 1

## Communication Interface

Intel® Wi-Fi 6 AX200, 802.11ax  
Bluetooth (v5.2)<sup>iv</sup>  
Optional: Dedicated GPS  
Optional: 4G LTE mobile broadband

## Security Feature

TPM 2.0

## Power

AC adapter (65W, 100-240VAC, 50 / 60Hz)  
Li-Ion battery (7.4V, typical 4200mAh; min. 4080mAh)<sup>i</sup>

## Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94")  
0.91 kg (2 lbs)<sup>i</sup>

## Rugged Feature

MIL-STD-810H certified  
IP65 certified  
Vibration & 6 feet (1.8m) drop resistant<sup>v</sup>  
ATEX & IECEx certified

## Environmental Specification

Temperature<sup>ii</sup>:  
- Operating: -21°C to 50°C / -6°F to 122°F  
- Storage: -51°C to 71°C / -60°F to 160°F  
Humidity:  
- 95% RH, non-condensing

## Explosion Protection

ATEX / IECEx zone 2 / 22  
Ex II 3G Ex ic IIC T4 Gc  
Ex II 3D Ex ic IIIB T130°C Dc

## Pre-installed Software

Getac Utility  
Getac Barcode Manager<sup>iii</sup>  
Getac Camera  
Optional: Absolute Persistence®

## Accessories

Battery (7.4V, typical 4200mAh; min. 4080mAh)  
AC Adapter (65W, 100-240VAC)  
Capacitive Stylus

## Optional:

Battery (7.4V, typical 4200mAh; min. 4080mAh)  
2nd Expanded Battery (14.4V, 2100 mAh)  
AC Adapter (65W, 100-240VAC)  
Digitizer Pen  
Capacitive Stylus

## Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

## Standard

3 years Bumper-to-Bumper

- i Weight and dimensions vary from configurations and optional accessories.
- ii Tested by an independent third-party test lab following MIL-STD-810H.
- iii Available when barcode reader option is selected
- iv Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- v Drop test results vary from configurations and optional accessories.

# T800-EX

## Fully Rugged Tablet



# Getac

## GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,  
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C  
Tel : +886 2 2785 7888  
globalmarketing@getac.com | www.getac.com



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.  
Information provided herewith is for reference only,  
available specification shall be subjected to quotation by request. V01M03Y21WWW